

Wireless module for mA signal



The Wireless Value DLXa measures process signals and transmits data to the base station. Sensing is performed using any available sensor with 0- 25 mA output. This allows connection of numerous commercially available sensors to monitor a wide variety of measurement parameters such as flow, level, pressure etc.

Overview

- Accurate and wireless sensing
- Battery lifetime up to 10 years
- Compatible with all WiSensys Base Stations
- 1.000 metre range (line of sight)

Applications

- Industrial

Specifications

- Ability to buffer 10.000 measurements
- Programmable measuring interval
- Attractive ABS enclosure
- Wall-mountable
- Easy to add sensors to operational system
- Unique network ID to avoid interference with other wireless systems

Sensor values are sent by the paired Base Station to:

- Wireless Value Online Portal (LAN of mobile provider)
- Wireless Value Online Portal (on premises)
- Modbus-network (IP or RS485)
- SensorGraph via serial interface or LAN

Wireless module for mA signal

Technical specifications

Design	Wireless module
Type	Process signal
Sensor type	External
Measurement range	
Range	0 – 25 mA
Measurement accuracy	
Accuracy	+/- 0.25% of range
Resolution	10 µA
Input impedance	43,2 Ohm
Overload protection	+100 mA, reverse polarity protected
Measurement interval	Configurable between 1 second and 255 minutes, default 2 minutes
Operating limits	-20 °C to +80 °C
Power	AA 3.6 V lithium battery or mains power supply
Memory	10.000 measurements
Radio standard	EN 300 220
Frequency	868 - 870MHz
Range	1.000 m with free line of sight
Housing class	IP65
Color	matt black
Dimensions	105(l) x 70(w) x 34(h) mm, excl. gland & wall mount
Weight	93 g (excluding battery)
Configuration	SensorGraph or Wireless Value Online Portal
Legislation	RED, CE
Ordering options	
Housing options	no
External antenna	no
Pressure relief valve	no
External power supply	no

