

# Wireless module for switching contact



The Wireless Value DLXct detects status, status changes and duration of a switching contact at times determined by the sample interval set by the user and transmits the status to the Base Station.

## Features

- Accurate and wireless sensing
- Battery lifetime up to 10 years
- Compatible with all Wireless Value Base Stations
- 1.000 metre range (line of sight)

## Applications

- Pharma & Lab
- Industrial

## Specifications

- Ability to buffer 10.000 measurements
- Programmable measuring interval
- Attractive ABS enclosure
- Wall-mountable
- Easy to add sensors to operational system
- User-replaceable battery
- Unique network ID to avoid interference with other wireless systems

## Sensor values are sent by the paired Base Station to:

- Wireless Value Online Portal (LAN of mobile provider)
- Wireless Value Online Portal (on premises)
- Modbus-network (IP or RS485)
- SensorGraph via serial interface or LAN

# Wireless module for switching contact

## Technical specifications

Model	wireless module
Type	contact signals
Sensortype	external
<b>Measurement range</b>	
Range	0 – 1
<b>Measurement accuracy</b>	
Detection levels	Closed: $V_{in} < 1\text{ V}$ , Open: $V_{in} > 2\text{ V}$
Detection frequency	1 Hz
Overload protection	+30 V
Measurement interval	Configurable between 1 second and 255 minutes, default 2 minutes
Operating limits	-20 °C to +80 °C
Power supply	1 AA 3,6 V lithium battery
Battery lifetime	up to 10 years at a measurement interval of 5 minutes
Memory	10.000 measurements
Radionorm	EN 300 220
Frequency	868 - 870 MHz
Legislation	RED, CE
Range	1.000 meter free line of sight
Housing class	IP65
Color	matt black
Dimensions	105(l) x 70(w) x 34(h) mm, excl. gland & wall mount
Gewicht	93 g (excluding battery)
Configuration	SensorGraph of Wireless Value Online Portal
<b>Ordering options</b>	
Housing options	no
External antenna	no
Pressure relief	no
External power supply	no

