



Wireless module for mV signal

The Wireless Value DLXac measures process signals and transmits data to the base station. Sensing is performed using available sensors/equipment with 0 - 1000 mV RMS output. A practical example is the current clamp for measuring electric current and based on that estimated energy consumption, signalling whether equipment is on/off/full load/part load etc.

Overview

- Accurate and wireless sensing
- Battery life >5 years
- Compatible with all WiSensys Base Stations
- 1.000 metre range (line of sight)

Applications

- Industrial

Specifications

- Ability to buffer 10.000 measurements
- Programmable measuring interval
- Attractive ABS enclosure
- Wall-mountable
- Easy to add sensors to operational system
- User-replaceable battery
- Unique network ID to avoid interference with other wireless systems

Sensor values are sent by the paired Base Station to:

- WebSensys (LAN or mobile carrier)
- WebSensys (On premises)
- MODBUS network (IP or serial)
- SensorGraph via serial interface or LAN RS485/422

Wireless module for mV signal

Technical specifications

Design	Wireless module
Type	Process signal
Sensor type	External
Measurement range	
Range	0 – 1000 mV RMS
Measurement accuracy	
Accuracy	+/- 0.25% of range
Resolution	1 mV
Input frequency	50 Hz – 1 kHz
Input impedance	1 MΩ
Overload protection	+10 mA
Measurement interval (M)	Configurable between 1 second and 255 minutes, default 2 minutes
Operating limits	-20 °C to +80 °C
Power	1 AA 3.6V Lithium battery
Memory	10.000 measurements
Radio standard	EN 300 220
Frequency	868 - 870MHz (915MHz where applicable)
Range	1.000 m with free line of sight
Housing	IP65
Color	WiSensys® Blue/Green
Dimensions	60(w) x 80(h) x 26(d) mm, excl. wall mount
Weight	80 g (excluding battery)
Configuration	SensorGraph or WebSensys
Regulatory	R&TTE, CE
Ordering options	
Housing options	Yes
External antenna	Yes
Pressure relief valve	Yes
External power supply	Yes

