



# Wireless module for contact switch

The Wireless Value DLXcc reads the status of a switch contact at points in time determined by the user-defined sample time and transmits this status to the base station.

## Overview

- Accurate and wireless sensing
- Battery life >5 years
- Compatible with all WiSensys Base Stations
- 1.000 metre range (line of sight)

## Applications

- Industrial
- Healthcare
- Laboratories

## Specifications

- Ability to buffer 10.000 measurements
- Programmable measuring interval
- Attractive ABS enclosure
- Wall-mountable
- Easy to add sensors to operational system
- User-replaceable battery
- Unique network ID to avoid interference with other wireless systems

## Sensor values are sent by the paired Base Station to:

- WebSensys (LAN or mobile carrier)
- WebSensys (On premises)
- MODBUS network (IP or serial)
- SensorGraph via serial interface or LAN RS485/422

# Wireless module for contact switch

## Technical specifications

|                             |  |
|-----------------------------|--|
| Design                      | Wireless module  |
| Type                        | Contact signals  |
| Sensor type                 | External   |
| <b>Measurement range</b>    |  |
| Range                       | 0 – 1  |
| <b>Measurement accuracy</b> |  |
| Detection levels            | Closed: $V_{in} < 1\text{ V}$ , Open: $V_{in} > 2\text{ V}$      |
| Overload protection         | +30 V  |
| Measurement interval (M)    | Configurable between 1 second and 255 minutes, default 2 minutes |
| Operating limits            | -20 °C to +80 °C   |
| Power                       | 1 AA 3.6V Lithium battery  |
| Memory                      | 10.000 measurements  |
| Radio standard              | EN 300 220   |
| Frequency                   | 868 - 870MHz (915MHz where applicable)                           |
| Range                       | 1.000 m with free line of sight                                  |
| Housing                     | IP65   |
| Color                       | WiSensys® Blue/Green   |
| Dimensions                  | 60(w) x 80(h) x 26(d) mm, excl. wall mount                       |
| Weight                      | 80 g (excluding battery)   |
| Configuration               | SensorGraph or WebSensys   |
| Regulatory                  | R&TTE, CE  |
| <b>Ordering options</b>     |  |
| Housing options             | Yes  |
| External antenna            | Yes  |
| Pressure relief valve       | Yes  |
| External power supply       | Yes  |

