



Wireless module for V signal

The Wireless Value DLXs measures process signals and transmits data to the base station. Sensing is performed using any available sensor with 0 – 4 V DC output. This allows connection of numerous commercially available sensors to monitor a wide variety of measurement parameters such as flow, level, pressure etc.

Overview

- Accurate and wireless sensing
- Compatible with all WiSensys Base Stations
- 1.000 metre range (line of sight)

Applications

- Industrial

Specifications

- Ability to buffer 10.000 measurements
- Programmable measuring interval
- Attractive ABS enclosure
- Wall-mountable
- Easy to add sensors to operational system
- Unique network ID to avoid interference with other wireless systems

Sensor values are sent by the paired Base Station to:

- WebSensys (LAN or mobile carrier)
- WebSensys (On premises)
- MODBUS network (IP or serial)
- SensorGraph via serial interface or LAN RS485/422

Wireless module for V signal

Technical specifications

Design	Wireless module
Type	Process signal 0-4 V
Sensor type	External
Measurement range	
Range	0-4 V
Measurement accuracy	
Accuracy	+/- 0,25 % of range
Resolution	3 mV
Input impedance	20 K Ω
Overload protection	30 V
Measurement interval (M)	Configurable between 1 second and 255 minutes, default 2 minutes
Operating limits	-20 °C to +80 °C
Power	External
Memory	10.000 measurements
Radio standard	EN 300 220
Frequency	868 - 870MHz (915MHz where applicable)
Range	1.000 m with free line of sight
Housing	IP65
Color	WiSensys® Blue/Green
Dimensions	60(w) x 80(h) x 26(d) mm, excl. wall mount
Weight	80 g (excluding battery)
Configuration	SensorGraph or WebSensys
Regulatory	R&TTE, CE
Ordering options	
Housing options	Yes
External antenna	Yes
Pressure relief valve	Yes
External power supply	Yes

