



Wireless soil moisture sensor

The Wireless Value DLXm-Teros10 easily measures soil moisture using a robust sensor. Measurement results are transmitted wirelessly to the base station where the data can be used for monitoring and analysis.

Features

- Simple soil moisture measurement
- Needle length 5,4 cm
- Battery life + 5 years
- Compatible with all Wireless Value base stations
- Transmission range 1,000 metres (unobstructed line of sight)

Applications

- Soil moisture measurement in covered cultivation
- Soil moisture measurement in soft fruit
- Soil moisture measurement in open field (avocado, orange, etc.)

Specifications

- Memory to store 10,000 measurements
- Adjustable measurement interval
- Attractive IP65 ABS enclosure
- Existing system can be easily expanded with additional sensors
- Battery replaceable by user

The connected base station sends the sensor values to:

- Wirelessvalue.online (LAN or mobile provider)
- Wirelessvalue.online (for direct connection to climate computer or irrigation system)

Wireless soil moisture sensor

Technical specifications

Model	Wireless Value module incl. Teros10 sensor
Type	advanced soil moisture sensor
Sensor type	SD112
Measurement range	
VWC	±0.03 m ³ /m ³ typical in mineral soils that have a solution EC <8 dS/m ±0.05 m ³ /m ³ typical in media that has a solution EC <8 dS/m
Measurement interval (M)	adjustable between 1 second and 255 minutes, standard 2 minutes
Operating limits	-20°C to +80°C
Power supply	1 AA 3.6 V lithium battery or 12V DC
Battery life	At least 5 years at 2-minute measurement interval
Memory	10,000 measurements
Order code Thailand	WSA52-DLXs-Teros10
Frequency plan	A5923-925 ("A52")
Frequency	924 MHz
Legislation	RED, CE
Range	1,000 m with unobstructed line of sight
Enclosure	IP65
Colour	matte black
Dimensions	105 (l) x 70 (w) x 32 (h) mm industrial: 190 (l) x 100 (w) x 43 (h) mm
Weight	67 grams, industrial: 270 grams
Configuration	SensorGraph
Ordering options	
Enclosure options	Wireless Value, Fibox or Hammond
External antenna	optional
Overpressure protection	optional
External power supply	optional

